



ELECTRICAL	
	CEILING FAN GLOBE 1
	FLUORESCENT FIXTURE
	VANITY BAR 3 LIGHT
	VANITY BAR 5 LIGHT
	WALL MOUNT 1
	FAN
	FAN-LIGHT
	LIGHT
	OUTLET
	OUTLET 220V
	OUTLET GFI
	OUTLET W.P. EXTERIOR
	SWITCH
	SWITCH 3 WAY

- NOTES:
- 1) OVERALL DIMENSIONS ARE TO OUTSIDE OF LOG WALL OR LOG SIDING PROFILE, NOT THE FLOOR SYSTEM.
 - 2) DOOR DIMENSIONS ARE UNIT SIZES. IF HOME TECHNOLOGY INTERNATIONAL, INC. DOORS ARE USED, ANY 3 PANEL HINGED DOOR SMALLER THAN 2'-0" WILL NOT HAVE HARDWARE PRE-INSTALLED. OWNER IS RESPONSIBLE FOR ROUTING AND INSTALLING DOOR HARDWARE. WINDOW SIZES SPECIFIED ARE DOUBLE HUNG WINDOWS BY ANDERSEN. CONSULT MANUFACTURER FOR ROUGH OPENING DIMENSIONS. ADD 3" TO WIDTH AND HEIGHT OF MANUFACTURERS ROUGH OPENING DIMENSIONS FOR 2x" BUCKS.
 - 3) ALL KITCHEN, BATH AND EXTERIOR ELECTRICAL OUTLETS ARE GFCI.
 - 4) LOCAL CODE MAY REQUIRE ALL 6'-0" TALL WINDOWS TO BE TEMPERED GLASS. CHECK WITH LOCAL CODES DEPARTMENT.
 - 5) A 2x6" PLUMBING WALL MAY BE REQUIRED, DEPENDING ON VENT STACK SIZE AND/OR LOCAL CODES.
 - 6) CEILING MAY NEED TO BE FURRED DOWN IN CERTAIN AREAS TO HIDE PLUMBING ABOVE.
 - 7) INSTALL SMOKE DETECTORS PER LOCAL CODE.
 - 8) VERIFY STAIR DESIGN WITH LOCAL CODES PRIOR TO CONSTRUCTION.
 - 9) CATHEDRAL/SLOPED CEILING AREA MAY REQUIRE AN EXTRA COURSE OF LOGS.
 - 10) IF NOT SPECIFIED ON PLANS, ALL PORCH AND/OR DECK RAILINGS AND STEPS ARE TO BE SPECIFIED BY OWNER.

LEGEND OF WALLS	
	6x12" D.T. H.H. EXT. LOGS
	9 COURSES
	STUD WALL W/LOG SIDING
	LOAD BEARING STUD WALL
	STUD WALL

LEGEND OF AREAS	
FIRST FLOOR	1471 S.F.
SECOND FLOOR	800 S.F.
TOTAL SQUARE FEET*	2271 S.F.
BASEMENT	1485 S.F.
PORCH	457 S.F.
DECK	1288 S.F.
GARAGE	N/A

*TOTAL SQUARE FEET EXCLUDES ATTIC AREA.

ORIGINAL OLD TIMER LOG HOMES AND SUPPLY INC.

RESIDENCE FOR:	SCALE:	DATE:	REVISED:	DRAWN BY:	PAGE:
THE STONEWOOD	1/4" = 1'-0"	2-23-06	3-1-06	M. M.	2 OF 8
FIRST FLOOR PLAN				APPROVED:	